

PRODUCT CERTIFICATE



Industrial / OTR Tyres

IND-1 HD (FL) MFL 438

LOAD GRIP+ MFL 438 is applicable for hay harvesting having rotor rakes/tedders as well as for logistics, particularly in forklifts. Its heavy construction with deep tread gives excellent stability in operation.



FORKLIFT

Salient Features

Feature	Advantage	Benefit
High-strength casing materials	High strength casing	High stability of the vehicle
Additional rubber at the shoulder	Sturdy buttress area	Better lateral stability
Chip and cut-resistant	Resistance to wear and tear	Extended mileage & durability

Technical Data

Size	Type	Recommended Rim	Alternate Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR	Load Index/Speed Symbol	Inflation Pressure	Recommended load, kg				
				SW	OD						Speed, km/h				
											LOAD WHEEL	STEER WHEEL	OTHER VEHICLES	OTHER VEHICLES	STATIC SIDE LOADER
250-15	TT	7.50 BD	7.0,7.5	235	745	-	-	16	153A2	8.3	4745	3650	4745	3650	5510

Size	Type	Recommended Rim	Alternate Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR	Load Index/Speed Symbol	Inflation Pressure	Recommended load, kg				
				SW	OD						Speed, km/h				
											LOAD WHEEL	STEER WHEEL	OTHER VEHICLES	OTHER VEHICLES	STATIC SIDE LOADER
250-15	TT	7.50 BD	7.0,7.5	235	745	-	-	20	159A2	10.0	5690	4375	5690	4375	6605