

PRODUCT CERTIFICATE



Industrial / OTR Tyres

L-2 SUPERCAT HD ML2 464

SUPER CAT HD ML2 464 is suitable for tuff road condition in Skid steer application. It's heavy construction ensures stability at any turn, extra rim guard also provides extra safety from damage. Its special compound with fusion layer lugs assure extended life and higher productivity.



BACKHOE



SKIDSTEER



DOZER

Salient Features

Feature	Advantage	Benefit
Reinforced fusion lug design	Suitable for rough surface	Improved life and enhanced productivity
Special RIM protector	Resist impact	Control damage
High strength casing materials	Strong casing	High stability during turning
Chip and cut resistant	Resistance to wear and tear	Extended mileage & durability

Technical Data

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.			
				SW	OD						Speed, km/h			
											Free Rolling			
mm	mm	mm	mm	Bar	10	15	25	30						
33X15.5-16.5	TL	13LB	-	400	857	390	2563	12	148A2	3.9	2780	2230	2030	1900
										4.3	2962	2369	2160	2020
										4.8	3150	2520	2300	2150