

PRODUCT CERTIFICATE



Industrial / OTR Tyres

IND1/3 RIM-GUARD MFL 437

RIM GUARD MFL 437 is applicable for hay harvesting having rotor rakes/tedders as well as for logistic particularly in forklift .It's heavy construction with deep tread gives excellent stability in operation.



FORKLIFT

Salient Features

Feature	Advantage	Benefit
High strength casing materials	High strength casing	High stability of vehicle
Additional rubber at shoulder	Sturdy buttress area	Better lateral stability
Chip and cut resistant	Resistance to wear and tear	Extended mileage & durability

Technical Data

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.			
									Speed, km/h			
									Load Wheel			
				SW	OD				All wheel	Load Wheel	Steer Wheel	Other Vehicle
				mm	mm			Bar	Static	10	10	10
8.15-15	TT	7	7.0BD	215	722	14	148A2	7.3	3425	2760	2230	2270
								8.1	3643	2950	2330	2330
								9	3875	3150	2426	2391

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.			
									Speed, km/h			
									Load Wheel			
				SW	OD				All wheel	Load Wheel	Steer Wheel	Other Vehicle
				mm	mm			Bar	Static	10	10	10
8.15-15	TT	7	7.0BD	215	722	16	152A2	8.5	3860	3110	2510	2550
								9.5	4105	3320	2620	2620
								10.5	4367	3550	2734	2694