

LD90**EM / INDUSTRIAL
TYRES**

New Product Code	Product Code	Tyre Size & Ply Rating	TL / TT	Inflated Unloaded Dimensions				Load & Pressure			
				Section Width	Overall Diameter	Load Index	Speed Symbol	Tyre Load Capacity	Tyre Pressure At Max. Load	Dynamic Rolling Circumference	Static Loaded Radius
				(mm)	(mm)			(Kg)	(Psi)		
6161242GTK	6055GTK	10-16.5 12PR	TL	256	793	138	A3	2360	84	2374	359
6162252GTK	6076GTK	12-16.5 14PR	TL	297	858	148	A3	3150	90	2558	385
6181042GTK	6115GTK	10.5/80-18 12PR	TL	271	892	135	A8	2180	62	2666	403
6182152GTK	6156GTK	12.5/80-18 14PR	TL	285	955	146	A8	3000	62	2844	428
6207062GTK	6277GTK	16.0/70-20 16PR	TL	385	1091	166	A2	5300	65	3244	487
6207162GTK	6277MGTK	405/70-20 16PR	TL	385	1091	166	A2	5300	65	3244	487
6243062GTK	6287GTK	15.5/80-24 16PR	TL	412	1269	162	A8	4750	72	3780	569
6245062GTK	6377GTK	16.0/70-24 16PR	TL	418	1200	169	A2	5800	65	3584	541
6245162GTK	6377MGTK	405/70-24 16PR	TL	418	1200	169	A2	5800	65	3584	541
6246062GTK	6397GTK	16.9-24 16PR	TL	429	1310	154	A8	3750	46	3895	585
6246162GTK	6397MGTK	440/80-24 16PR	TL	429	1310	154	A8	3750	46	3895	585
6247052GTK	6566GTK	17.5L-24 14PR	TL	475	1277	154	A8	3750	46	3802	572
6248052GTK	6576GTK	19.5L-24 14PR	TL	495	1314	154	A8	3750	38	3907	587
6251052GTK	6816GTK	15.5-25 14PR	TL	400	1286	173	A2	6500	68	3836	578
6261052GTK	6516GTK	18.4-26 14PR	TL	467	1425	160	A8	4500	42	4237	636
6281052GTK	6616GTK	16.9-28 14PR	TL	429	1410	156	A8	4000	43	4210	635
6281152GTK	6616MGTK	440/80-28 14PR	TL	429	1410	156	A8	4000	43	4210	635
6301062GTK	6957GTK	16.9-30 16PR	TL	418	1466	156	A8	4000	47	4384	663

The product marked as blue will be launched during 2021.