

PRODUCT CERTIFICATE



Industrial / OTR Tyres

L-2 SUPERCAT HD ML2 464

SUPER CAT HD ML2 464 is suitable for tuff road condition in Skid steer application. It's heavy construction ensures stability at any turn , extra rim guard also provides extra safety from damage. Its special compound with fusion layer lugs assure extended life and higher productivity.



BACKHOE



SKIDSTEER



DOZER

Salient Features

Feature	Advantage	Benefit
Reinforced fusion lug design	Suitable for rough surface	Improved life and enhanced productivity
Special RIM protector	Resist impact	Control damage
High strength casing materials	Strong casing	High stability during turning
Chip and cut resistant	Resistance to wear and tear	Extended mileage & durability

Technical Data

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.			
				SW	OD						Speed, km/h			
											Free Rolling			
						mm	mm				mm	mm		
14-17.5	TL	10.5	-	350	920	420	2743	14	155A2	4.5	3430	2740	2500	2330
										5.0	3643	2915	2660	2480
										5.5	3875	3100	2830	2640

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.			
				SW	OD						Speed, km/h			
											Free Rolling			
						mm	mm				mm	mm		
14-17.5	TL	10.5	-	350	920	420	2743	16	158A2	5.0	3760	3010	2740	2560
										5.6	3996	3197	2910	2720
										6.2	4250	3400	3100	2890