

PRODUCT CERTIFICATE



Industrial / OTR Tyres

L-2 SKID STAR ML2 455

SKID STAR ML2 455 is suitable for tuff road condition in Skid steer & NHS application. It's heavy construction ensures stability at any turn, extra rim guard also provides extra safety from damage. Its special compound with stepped lugs assure extended life and higher productivity.



BACKHOE



SKIDSTEER



DOZER

Salient Features

Feature	Advantage	Benefit
Reinforced fusion lug design	Suitable for rough surface	Improved life and enhanced productivity
Special RIM protector	Resist impact	Control damage
Chip and cut resistant	Resistance to wear and tear	Extended mileage & durability

Technical Data

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs			
				SW	OD						Speed, km/h			
											Free Rolling			
mm	mm	mm	mm	10	15	25	30							
10-16.5	TL	8.25	-	263	780	356	2286	10	134A2	Bar	1870	1500	1370	1280
										4.2	1993	1598	1460	1360
										4.7	2120	1700	1550	1450

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs			
				SW	OD						Speed, km/h			
											Free Rolling			
mm	mm	mm	mm	10	15	25	30							
10-16.5	TL	8.25	-	263	780	356	2286	12	138A2	Bar	2090	1670	1520	1420
										5.0	2219	1777	1620	1510
										5.6	2360	1890	1720	1610