

SM-I25 (R-4)



Specially designed for backhoe and telehandler applications. Offers ultimate resistance to cuts, tears, chips and chunks with its exceptional tread compound and wide lugs. Strong carcass structure ensures longevity.



TIRE SIZE	PR	TT/ TL	LOAD INDEX	SPEED SYMBOL	RIM		INFLATED DIMENSIONS (NO LOAD)		INFLATED DIMENSIONS (W/LOAD)		TREAD DEPTH (MM)	INFLATING PRESSURE (psi)	LOAD CAPACITY PER TIRE (KG)							
					RECOM. (INCHES)	PERMITTED (INCHES)	OUTER DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOADED RADIUS (MM)	DYNAMIC RADIUS CIRCLE (MM)			Speed (KM/H)							
													10	15	20	25	30	40	50	65
12.5/80-18	14	TL	146	A8	W9	11.00	987	308	446	2862	27	62	3750	3390	3270	3180	3120	3000	2700	-
340/80-18	12	TL	142	A8	11	W10; W11	1001	343	452	2903	27	54	3315	2995	2890	2810	2755	2650	2385	-
405/70-20	14	TL	154	A8	13	12SDC ; 13SDC ; 14	1075	418	495	3103	33	51	4690	4240	4090	3975	3900	3750	3375	-
16.0/70-20	14	TL	154	A8	13	12SDC ; 13SDC ; 14	1075	418	495	3103	33	51	4690	4240	4090	3975	3900	3750	3375	-
16.0/70-20	16	TL	156	A8	13	12SDC ; 13SDC ; 14	1075	418	495	3103	33	58	5000	4520	4360	4240	4160	4000	3600	-
16.0/70-24	14	TL	152	B	13.00	13 (DC) - 13 (SDC)	1178	407	542	3405	34	51	-	3975	3905	3835	3765	3655	3550	-
405/70-24	14	TL	152	B	13.00	13 (DC) - 13 (SDC)	1178	407	542	3405	34	51	-	3975	3905	3835	3765	3655	3550	-
14.5-20	14	TT	143	D	11	11 SDC	1095	355	495	3176	28	51	4495	4085	3545	3350	3135	2890	2835	2725
14.5-20	14	TL	143	D	11	11 SDC	1095	355	495	3176	28	51	4495	4085	3545	3350	3135	2890	2835	2725
19.5L-24	12	TL	151	A8	DW16A	-	1314	495	594	3810	29	34	4315	3890	3760	3655	3590	3450	3105	-
440/80-24	12	TL	149	A8	DW14L	DW13; DW13L; DW15L	1314	441	594	3810	30	38	4065	3675	3545	3445	3380	3250	2925	-
16.9-24	12	TL	149	A8	DW15L	DW14L	1310	429	592	3799	30	38	4065	3675	3545	3445	3380	3250	2925	-
16.9-24	14	TL	152	A8	DW15L	DW14L	1310	429	592	3799	30	43	4440	4010	3870	3760	3690	3550	3195	-
16.5/85-24	12	TL	149	A8	W13L	W15L ; W14L	1322	417	597	3834	30	41	4065	3675	3545	3445	3380	3250	2925	-
16.5/85-24	16	TL	156	A8	W13L	W15L ; W14L	1322	417	597	3834	30	54	5000	4520	4360	4240	4160	4000	3600	-
16.9-28	12	TT	152	A8	DW15L	DW14L	1410	429	643	4089	30	38	4440	4012	3870	3765	3690	3550	3195	-
16.5/85-28	12	TL	152	A8	DW15L	DW14L	1410	429	643	4089	30	38	4440	4012	3870	3765	3690	3550	3195	-
16.9-28	14	TL	156	A8	DW15L	DW14L	1410	429	643	4089	30	44	5000	4520	4360	4240	4160	4000	3600	-
440/80-28	12	TL	152	A8	DW14L	DW13; DW13L; DW15L	1415	441	645	4104	30	38	4440	4012	3870	3765	3690	3550	3195	-
480/80-26	14	TL	158	A8	DW15L	DW16L	1428	479	647	4141	32	42	5310	4800	4630	4505	4420	4250	3825	-
18.4-26	12	TL	156	A8	DW16L	DW15L	1425	467	644	4133	32	36	5000	4520	4360	4240	4160	4000	3600	-
18.4-26	14	TL	158	A8	DW16L	DW15L	1425	467	644	4133	32	42	5310	4800	4630	4505	4420	4250	3825	-
18.4-26	16	TL	160	A8	DW16L	DW15L	1425	467	644	4133	32	48	5625	5085	4905	4770	4680	4500	4050	-

