

PRODUCT CERTIFICATE



Industrial / OTR Tyres

IND-1 HD (FL) MFL 438

LOAD GRIP+ MFL 438 is applicable for hay harvesting having rotor rakes/tedders as well as for logistics, particularly in forklifts. Its heavy construction with deep tread gives excellent stability in operation.



FORKLIFT

Salient Features

Feature	Advantage	Benefit
High-strength casing materials	High strength casing	High stability of the vehicle
Additional rubber at the shoulder	Sturdy buttress area	Better lateral stability
Chip and cut-resistant	Resistance to wear and tear	Extended mileage & durability

Technical Data

Size	Type	Recommended Rim	Alternate Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR	Load Index/Speed Symbol	Inflation Pressure	Recommended load, kg				
				SW	OD						Speed, km/h				
											LOAD WHEEL	STEER WHEEL	OTHER VEHICLES	OTHER VEHICLES	STATIC SIDE LOADER
300-15	TT	8.00 BD	8	295	840	-	-	18	163A2	7.5	6335	4875	6335	4875	7360

Size	Type	Recommended Rim	Alternate Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR	Load Index/Speed Symbol	Inflation Pressure	Recommended load, kg				
				SW	OD						Speed, km/h				
											LOAD WHEEL	STEER WHEEL	OTHER VEHICLES	OTHER VEHICLES	STATIC SIDE LOADER
300-15	TT	8.00 BD	8	295	840	-	-	20	166A2	7.5	6890	5300	6890	5300	8000