

PRODUCT CERTIFICATE



Industrial / OTR Tyres

R-4 SUPER CAT ATU 410

SUPER CAT ATU-410 is designed for the backhoe and wheel loader suitable for different aggressive surfaces. The tyre is usable in the front axel in four-wheel drive application. Engineered strong carcass and cut & chip resistant pattern ensures full traction



BACKHOE



GRADER



DOZER

Salient Features

Feature	Advantage	Benefit
Diversified tread pattern	Optimum traction	Suitable for straight and turning movement
Cut & chip resistant	Resistance to wear and tear	Extended mileage & durability
Strong casing	Suitable for carry high load applications	Higher reliability at difficult applications

Technical Data

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.				
				Speed, km/h											
				Mixed Application											
		SW	OD												
		mm	mm	mm	mm										
12.5/80-18	TL	W9	W11	308	980	437.9	2896	12	148A6/144A8	Bar	Static	10	20	30	40
										3.3	5920	4110	3290	2960	2664
										3.7	7340	4160	3470	3150	2835

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.				
				Speed, km/h											
				Mixed Application											
		SW	OD												
		mm	mm	mm	mm										
12.5/80-18	TL	W9	W11	308	980	437.9	2896	14	151A6/147A8	Bar	Static	10	20	30	40
										3.9	6480	4500	3600	3240	2916
										4.3	8040	4550	3800	3450	3105

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.				
				Speed, km/h											
				Mixed Application											
		SW	OD												
		mm	mm	mm	mm										
12.5/80-18	TL	W9	W11	308	980	437.9	2896	16	154A6/150A8	Bar	Static	10	20	30	40
										4.4	7060	4910	3920	3530	3177
										4.9	8740	4950	4130	3750	3375