

PRODUCT CERTIFICATE



Industrial / OTR Tyres

L-4 / L-5 THE BEAST HD ATU 482

THE BEASE HD ATU-482 is a unique design for heavy load and challenging surface conditions. The Deep tread with extra under rubber ensures puncture/damage resistance and good traction. ATU-482 provides a thick & reinforced sidewall which guarantees better stability and handling. Engineered strong carcass confirms the heavy load-carrying capacity and durability.



BACKHOE



GRADER



DOZER

Salient Features

Feature	Advantage	Benefit
Thicker central tread	Wider contact patch at the base	Better stability and mileage
Strong & reinforced sidewall	High stiffness buttress	Better stability of vehicle
Chip and cut resistant	Resistance to wear and tear	Extended mileage & durability

Technical Data

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.	
				SW	OD						Speed, km/h	
				mm	mm						Mixed Application	
12.5/80-18	TL	W9	W11	308	980	437.9	2896	12	148A6/144A8	3.7	30	40
										Bar	3150	2835

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.	
				SW	OD						Speed, km/h	
				mm	mm						Mixed Application	
12.5/80-18	TL	W9	W11	308	980	437.9	2896	14	152A6/148A8	4.3	30	40
										Bar	3550	3195

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.	
				SW	OD						Speed, km/h	
				mm	mm						Mixed Application	
12.5/80-18	TL	W9	W11	308	980	437.9	2896	16	154A6/150A8	4.9	30	40
										Bar	3750	3375