

# PRODUCT CERTIFICATE



## Industrial / OTR Tyres

**IND1/3 RIM-GUARD MFL 437**

**RIM GUARD MFL 437** is applicable for hay harvesting having rotor rakes/tedders as well as for logistic particularly in forklift .It's heavy construction with deep tread gives excellent stability in operation.



FORKLIFT

## Salient Features

Feature	Advantage	Benefit
High strength casing materials	High strength casing	High stability of vehicle
Additional rubber at shoulder	Sturdy buttress area	Better lateral stability
Chip and cut resistant	Resistance to wear and tear	Extended mileage & durability

## Technical Data

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.			
									Speed, km/h			
									Load Wheel			
				SW	OD				All wheel	Load Wheel	Steer Wheel	Other Vehicle
				mm	mm			Bar	Static	10	10	10
5.00-8	TT	3.0D	3.25I	135	467	10	114A2	8.1	1283	1030	830	840
								9.0	1365	1100	870	870
								10	1451	1180	909	896

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.			
									Speed, km/h			
									Load Wheel			
				SW	OD				All wheel	Load Wheel	Steer Wheel	Other Vehicle
				mm	mm			Bar	Static	10	10	10
5.00-8	TT	3.0D	3.25I	135	467	12	117A2	8.5	1397	1120	910	920
								9.5	1486	1200	950	950
								10.5	1581	1285	989	975