

PRODUCT CERTIFICATE

Industrial / OTR Tyres

G-2/L-2 SUPER GRADER MG2 419



MG2-419 SUPER GRADER is suitable for the backhoe and wheel loader. MG2-419 SUPER GRADER is developed to impart smooth and trouble-free service in severe operating conditions like construction, site preparation, road building, and other soft or muddy environments. Engineered strong carcass and cut & chip resistant pattern ensures full traction and life in the road, soil, sand, rock, and gravel. Wide lug & shoulder help to get better traction in Off-road applications.



BACKHOE



GRADER



DOZER

Salient Features

Feature	Advantage	Benefit
Deep open shoulder	Enhanced traction	Suitable for loose soil applications
Cut & chip resistant	Resistance to wear and tear	Extended mileage & durability
Strong casing	Suitable for carry high load applications	Higher reliability at difficult applications

Technical Data

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.					Inflation Pressure	Recommended Load, kgs			
				SW	OD						Speed, km/h						Bar	Speed, km/h		
											Grader Application								Loader Application	
											40	50	60	65	10					
15.5-25	TL	12.00/1.3	-	384	1270	572	3772	12	142A8/168A2	Bar	40	50	60	65	Bar	10				
										1.8	2321	2110	1990	1830	3.2	4904				
										2.0	2480	2260	2080	1880	3.6	5240				
										2.25	2650	2420	2173	1935	4	5600				

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.					Inflation Pressure	Recommended Load, kgs			
				SW	OD						Speed, km/h						Bar	Speed, km/h		
											Grader Application								Loader Application	
											40	50	60	65	10					
15.5-25	TL	12.00/1.3		384	1270	572	3772	16	147A8/173A2	Bar	40	50	60	65	Bar	10				
										2.6	2693	2450	2320	2130	4.3	5692				
										2.9	2878	2620	2420	2190	4.7	6083				
										3.2	3075	2800	2521.5	2245	5.25	6500				