

Premium 2-stage solid resilient tire.

- ▶ Premium natural rubber compounds:
 - Cut and tear-resistant tread
 - Chunk-resistant non-marking (NM)
 - Premium nylon reinforced base compound
- ▶ 2-stage compound construction with steel torque rings
- ▶ Excellent stability
- ▶ Deep tread configuration for superior traction
- ▶ Available in both Standard and Swift (Clip/Halo/LOC) bead set configuration



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	RIM	TYPE		O.D.		S.W.		T.D.		L.C.C. (LBS/KG)	
		STD	SWIFT	in	mm	in	mm	in	mm	15 mph/25 kph	
										LOAD WHEELS	STEER WHEELS
100/80-8 SM	2.50C	*		14.3	363	4.3	109	0.9	23	2205/1000	1700/770
15 x 4.5-8 (125/75-8)	3.00D	*	*	14.7	373	4.2	107	1.1	28	2290/1040	1765/800
	3.25I	*		14.7	373	4.2	107	1.1	28	2290/1040	1765/800
15 x 4.5-8 (125/75-8) RIB	2.50C	*		14.7	373	4.2	107	1.1	28	2290/1040	1765/800
	3.00D	*	*	14.7	373	4.2	107	1.1	28	2290/1040	1765/800
400-8	3.00D	*	*	15.8	401	3.8	97	1.4	36	2095/950	1610/730
400-8 RIB	3.00D	*	*	15.8	401	3.8	97	1.4	36	2095/950	1610/730
5.00-8	3.00D	*	*	17.7	450	4.5	114	1.4	36	3120/1415	2400/1090
16 x 6-8	4.33R	*	*	16.1	409	5.5	140	1.2	30	3210/1455	2470/1120
18 x 7-8	4.33R	*	*	17.6	447	5.7	145	1.5	38	4730/2145	3640/1650
140/55-9	4.00E	*	*	14.6	371	4.8	122	1.1	28	2580/1170	1985/900
6.00-9	4.00E	*	*	20.5	521	5.2	132	1.6	41	4155/1885	3200/1450
6.00-9 RIB	4.00E	*	*	20.5	521	5.2	132	1.6	41	4155/1885	3200/1450
21 x 8-9	6.00E	*	*	20.2	513	7.0	178	2.0	51	6075/2755	4675/2120
200/50-10	6.50F	*	*	17.8	452	7.2	183	1.6	41	5445/2470	4190/1900
6.50-10	5.00F	*	*	22.3	566	6.0	152	2.0	51	5160/2340	3970/1800
23 x 9-10 (255/75-10)	6.50F	*	*	22.7	576	7.4	188	2.2	56	7595/3445	5840/2650
7.00-12	5.00S	*	*	25.4	645	6.4	163	2.1	53	6440/2920	4940/2240
27 x 10-12	8.00G	*	*	26.4	670	9.3	236	2.2	56	8600/3900	6610/3000



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	RIM	TYPE		O.D.		S.W.		T.D.		L.C.C. (LBS/KG)	
		STD	SWIFT	in	mm	in	mm	in	mm	15 mph/25 kph	
										LOAD WHEELS	STEER WHEELS
28 x 9-15 (8.15-15)	7.00	*	*	26.9	683	8.0	203	2.0	51	8600/3900	6610/3000
7.00-15	5.50	*	*	28.3	719	6.6	168	2.2	56	7815/3545	6010/2725
7.50-15	5.50	*	*	29.4	747	7.4	188	2.3	58	8600/3900	6610/3000
	6.50	*	*	29.4	747	7.4	188	2.3	58	8600/3900	6610/3000
8.25-15	5.50	*	*	31.7	805	7.6	193	2.8	71	10175/4615	7825/3550
	6.50	*	*	31.7	805	7.6	193	2.8	71	10470/4750	8045/3650
250-15 (250/70-15)	7.00	*	*	28.0	711	8.2	208	2.1	53	10470/4750	8045/3650
	7.50	*	*	28.0	711	8.2	208	2.1	53	10470/4750	8045/3650
300-15 (315/70-15)	8.00	*	*	31.8	808	9.5	241	2.5	63	12895/5850	9920/4500
355/65-15 (350-15)	9.75	*	*	32.0	813	11.5	292	3.5	89	17195/7800	13230/6000
10.00-20	7.00	*		40.4	1026	9.8	249	3.1	79	13230/6000	11025/5000
	7.50	*		40.4	1026	9.8	249	3.1	79	13230/6000	11025/5000
	8.00	*		40.4	1026	9.8	249	3.1	79	13230/6000	11025/5000
12.00-20	8.00	*		42.7	1084	10.9	277	3.4	86	16660/7560	13890/6300
	8.50	*		42.7	1084	10.9	277	3.4	86	16660/7560	13890/6300
	10.00	*		42.7	1084	10.9	277	3.4	86	17190/7800	14330/6500

