

Standard E3/L3 rock lug pattern combines excellent traction and high resistance to wear and cutting.

- ▶ Excellent traction in all off-road conditions
- ▶ Thick undertread for improved puncture resistance
- ▶ Wear and cut-resistant tread compound



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	P.R.	TYPE	RIM	O.D.	S.W.	T.D.	INFLATION PRESSURE	L.C.C. (LBS/KG)	INFLATION PRESSURE	L.C.C. (LBS/KG)	L.I.
				in	in	32nds	psi	5 mph	psi	30 mph	
				mm	mm	mm	KPa	10 kph	KPa	50 kph	
15.5-25	12	TL	12.00/1.3	50.5	15.6	31	58	12300	36	7150	168A2/149B
				1283	395	25	400	5600	250	3250	
17.5-25	16	TL	14.00/1.5	52.8	17.2	33	69	16100	44	9350	177A2/158B
				1341	437	26	475	7300	300	4250	
	20	TL	14.00/1.5	53.3	17.9	33	83	18200	58	11000	181A2/164B
				1354	456	26	575	8250	400	5000	
20.5-25	16	TL	17.00/2.0	58.2	20.9	37	51	18200	40	12000	181A2/167B
				1479	532	29	350	8250	275	5450	
	20	TL	17.00/2.0	58.1	21.2	37	65	20900	47	13200	186A2/170B
				1477	538	29	450	9500	325	6000	
23.5-25	16	TL	19.50/2.5	63.2	23.9	44	44	20900	33	13600	186A2/171B
				1605	607	35	300	9500	225	6150	
	20	TL	19.50/2.5	63.4	22.9	44	54	24000	44	16100	191A2/177B
				1611	583	35	375	10900	300	7300	
	28	TL	19.50/2.5	63.5	23.2	44	80	30000	58	19300	199A2/183B
				1612	589	35	550	13600	400	8750	
26.5-25	20	TL	22.00/3.0	69	26.6	48	51	29100	36	18200	198A2/181B
				1752	676	38	350	13200	250	8250	
	24	TL	22.00/3.0	68.8	26.1	48	58	30900	44	20400	200A2/185B
				1747	662	38	400	14000	300	9250	
	28	TL	22.00/3.0	68.3	27.1	48	69	34200	51	22000	203A2/188B
				1736	688	38	475	15500	350	10000	

