

# PRODUCT CERTIFICATE



## Industrial / OTR Tyres

**L-2 SUPERCAT HD ML2 464**

**SUPER CAT HD ML2 464** is suitable for tuff road condition in Skid steer application. It's heavy construction ensures stability at any turn, extra rim guard also provides extra safety from damage. Its special compound with fusion layer lugs assure extended life and higher productivity.



BACKHOE



SKIDSTEER



DOZER

## Salient Features

Feature	Advantage	Benefit
Reinforced fusion lug design	Suitable for rough surface	Improved life and enhanced productivity
Special RIM protector	Resist impact	Control damage
High strength casing materials	Strong casing	High stability during turning
Chip and cut resistant	Resistance to wear and tear	Extended mileage & durability

## Technical Data

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.			
				Speed, km/h										
				Free Rolling										
				SW	OD									
mm		mm		mm		mm		Bar	10	15	25	30		
12-16.5	TL	9.75	-	314	845	381	2434	12	145A2	4.5	2560	2050	1870	1750
										5.0	2727	2181	1990	1860
										5.5	2900	2320	2120	1980

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.			
				SW	OD						Speed, km/h			
											Free Rolling			
				mm	mm	mm	mm			Bar	10	15	25	30
12-16.5	TL	9.75	-	314	845	381	2434	14	147A2	5.0	2720	2170	1980	1850
										5.6	2891	2313	2110	1970
										6.2	3075	2460	2240	2100