

PRODUCT CERTIFICATE



Industrial / OTR Tyres

IND1/3 RIM-GUARD MFL 437

RIM GUARD MFL 437 is applicable for hay harvesting having rotor rakes/tedders as well as for logistic particularly in forklift .It's heavy construction with deep tread gives excellent stability in operation.



FORKLIFT

Salient Features

Feature	Advantage	Benefit
High strength casing materials	High strength casing	High stability of vehicle
Additional rubber at shoulder	Sturdy buttress area	Better lateral stability
Chip and cut resistant	Resistance to wear and tear	Extended mileage & durability

Technical Data

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.			
									Speed, km/h			
									Load Wheel			
				SW	OD				All wheel	Load Wheel	Steer Wheel	Other Vehicle
				mm	mm			Bar	Static	10	10	10
7.00-12	TT	5.00S	-	188	695	12	136A2	6.9	2436	1970	1590	1620
								7.7	2591	2100	1660	1660
								8.5	2755	2240	1725	1700

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.			
									Speed, km/h			
									Load Wheel			
				SW	OD				All wheel	Load Wheel	Steer Wheel	Other Vehicle
				mm	mm			Bar	Static	10	10	10
7.00-12	TT	5.00S	-	188	695	14	137A2	7.3	2501	2010	1630	1660
								8.1	2660	2150	1700	1700
								9	2829	2300	1771	1746