

PRODUCT CERTIFICATE



Industrial / OTR Tyres

IND1/3 RIM-GUARD MFL 437

RIM GUARD MFL 437 is applicable for hay harvesting having rotor rakes/tedders as well as for logistic particularly in forklift .It's heavy construction with deep tread gives excellent stability in operation.



FORKLIFT

Salient Features

Feature	Advantage	Benefit
High strength casing materials	High strength casing	High stability of vehicle
Additional rubber at shoulder	Sturdy buttress area	Better lateral stability
Chip and cut resistant	Resistance to wear and tear	Extended mileage & durability

Technical Data

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.			
				SW	OD				Speed, km/h			
									Load Wheel			
				mm	mm				All wheel	Load Wheel	Steer Wheel	Other Vehicle
6.00-9	TT	4.00E	-	158	544	10	121A2	Bar	Static	10	10	10
								6.9	1577	1270	1020	1040
								7.7	1677	1360	1070	1070
								8.5	1784	1450	1117	1101

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.			
				SW	OD				Speed, km/h			
									Load Wheel			
				mm	mm				All wheel	Load Wheel	Steer Wheel	Other Vehicle
6.00-9	TT	4.00E	-	158	544	12	123A2	Bar	Static	10	10	10
								8.1	1685	1360	1090	1110
								9.0	1793	1450	1140	1140
								10	1907	1550	1194	1176