

# PRODUCT CERTIFICATE



## Industrial / OTR Tyres

**IND1/3 RIM-GUARD MFL 437**

**RIM GUARD MFL 437** is applicable for hay harvesting having rotor rakes/tedders as well as for logistic particularly in forklift .It's heavy construction with deep tread gives excellent stability in operation.



FORKLIFT

## Salient Features

Feature	Advantage	Benefit
High strength casing materials	High strength casing	High stability of vehicle
Additional rubber at shoulder	Sturdy buttress area	Better lateral stability
Chip and cut resistant	Resistance to wear and tear	Extended mileage & durability

## Technical Data

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.			
									Speed, km/h			
									Load Wheel			
				SW	OD				All wheel	Load Wheel	Steer Wheel	Other Vehicle
				mm	mm			Bar	Static	10	10	10
6.50-10	TT	5.00F	5.5F	185	595	10	124A2	6.3	1740	1400	1130	1150
								7.0	1850	1500	1180	1180
								7.8	1968	1600	1232	1214

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.			
									Speed, km/h			
									Load Wheel			
				SW	OD				All wheel	Load Wheel	Steer Wheel	Other Vehicle
				mm	mm			Bar	Static	10	10	10
6.50-10	TT	5.00F	5.5F	185	595	12	128A2	7.3	1957	1570	1270	1290
								8.1	2082	1680	1330	1330
								9	2214	1800	1386	1366