

# Camso MPT 732



## Load capacity per tire in kilogram (kg)

### 280/80-18 IND : Cyclic load service (Pick & Carry)

Inflation Pressure		Load Index (A8)	Static	Creep [1]	5 km/h	10 km/h	15 km/h	20 km/h	25 km/h	30 km/h	35 km/h	40 km/h	45 km/h	50 km/h
[kPa]	[PSI]				[2.5 mph]	[5 mph]	[10 mph]	[12.5 mph]	[16 mph]	[20 mph]	[22 mph]	[25 mph]	[28 mph]	[30 mph]
120	17		1930		1405*	1260**	1125	1035	930	900	865	840	805	765
160	23		2345		1705*	1530**	1365	1255	1130	1090	1050	1020	980	930
200	29		2575		1870*	1680**	1500	1380	1245	1200	1155	1120	1075	1020
240	35		2990		2170*	1950**	1740	1600	1445	1390	1340	1300	1250	1185
280	41		3405		2470*	2220**	1985	1820	1645	1585	1525	1480	1420	1345
320	46		3820		2770*	2490**	2225	2040	1845	1775	1710	1660	1595	1510
360	52		4185		3040*	2730**	2440	2240	2020	1945	1875	1820	1745	1655
400	58	132	4600		3340*	3000**	2680	2460	2220	2140	2060	2000	1920	1820

### 280/80-18 IND : Constant load service (Transport)

Inflation Pressure		Load Index (A8)	Static	Creep [1]	5 km/h	10 km/h	15 km/h	20 km/h	25 km/h	30 km/h	35 km/h	40 km/h	45 km/h	50 km/h
[kPa]	[PSI]				[2.5 mph]	[5 mph]	[10 mph]	[12.5 mph]	[16 mph]	[20 mph]	[22 mph]	[25 mph]	[28 mph]	[30 mph]
120	17		1930		1220	1050	950	915	890	875	855	840	805	765
160	23		2345		1480	1275	1155	1110	1080	1060	1040	1020	980	930
200	29		2575		1625	1400	1265	1220	1185	1165	1140	1120	1075	1020
240	35		2990		1885	1625	1470	1415	1380	1350	1325	1300	1250	1185
280	41		3405		2145	1850	1670	1615	1570	1540	1510	1480	1420	1345
320	46		3820		2405	2075	1875	1810	1760	1725	1695	1660	1595	1510
360	52		4185		2640	2275	2055	1985	1930	1895	1855	1820	1745	1655
400	58	132	4600		2900	2500	2260	2180	2120	2080	2040	2000	1920	1820

[1] Creep means a movement of equipment at a very low speed (commonly not over 120 m in 60 minutes)

\* Cyclic: One way distance up to 150 m (500 feet); \*\* Cyclic: One way distance up to 600 m (2000 feet)

IMPORTANT: Recommendations and technical data are subject to change without prior notice.

# Camso MPT 732



## Load capacity per tire in kilogram (kg)

### 320/80-18 IND : Cyclic load service (Pick & Carry)

Inflation Pressure		Load Index (A8)	Static	Creep [1]	5 km/h	10 km/h	15 km/h	20 km/h	25 km/h	30 km/h	35 km/h	40 km/h	45 km/h	50 km/h
[kPa]	[PSI]				[2.5 mph]	[5 mph]	[10 mph]	[12.5 mph]	[16 mph]	[20 mph]	[22 mph]	[25 mph]	[28 mph]	[30 mph]
120	17		2345		1705*	1530**	1365	1255	1130	1090	1050	1020	980	930
160	23		2850		2070*	1860**	1660	1525	1375	1325	1275	1240	1190	1130
200	29		3130		2270*	2040**	1820	1675	1510	1455	1400	1360	1305	1240
240	35		3635		2640*	2370**	2115	1945	1755	1690	1625	1580	1515	1440
280	41		4140		3005*	2700**	2410	2215	2000	1925	1855	1800	1730	1640
320	46		4635		3365*	3025**	2700	2480	2235	2155	2075	2015	1935	1835
360	52		5085		3690*	3315**	2960	2720	2455	2365	2275	2210	2120	2010
400	58	139	5590		4060*	3645**	3255	2990	2695	2600	2505	2430	2335	2210

### 320/80-18 IND : Constant load service (Transport)

Inflation Pressure		Load Index (A8)	Static	Creep [1]	5 km/h	10 km/h	15 km/h	20 km/h	25 km/h	30 km/h	35 km/h	40 km/h	45 km/h	50 km/h
[kPa]	[PSI]				[2.5 mph]	[5 mph]	[10 mph]	[12.5 mph]	[16 mph]	[20 mph]	[22 mph]	[25 mph]	[28 mph]	[30 mph]
120	17		2345		1480	1275	1155	1110	1080	1060	1040	1020	980	930
160	23		2850		1800	1550	1400	1350	1315	1290	1265	1240	1190	1130
200	29		3130		1970	1700	1535	1480	1440	1415	1385	1360	1305	1240
240	35		3635		2290	1975	1785	1720	1675	1645	1610	1580	1515	1440
280	41		4140		2610	2250	2035	1960	1910	1870	1835	1800	1730	1640
320	46		4635		2920	2520	2275	2195	2135	2095	2055	2015	1935	1835
360	52		5085		3205	2765	2495	2410	2345	2300	2255	2210	2120	2010
400	58	139	5590		3525	3040	2745	2650	2575	2525	2480	2430	2335	2210

[1] Creep means a movement of equipment at a very low speed (commonly not over 120 m in 60 minutes)

\* Cyclic: One way distance up to 150 m (500 feet); \*\* Cyclic: One way distance up to 600 m (2000 feet)

IMPORTANT: Recommendations and technical data are subject to change without prior notice.

# Camso MPT 732



## Load capacity per tire in kilogram (kg)

### 340/80-18 IND : Cyclic load service (Pick & Carry)

Inflation Pressure		Load Index (A8)	Static	Creep [1]	5 km/h	10 km/h	15 km/h	20 km/h	25 km/h	30 km/h	35 km/h	40 km/h	45 km/h	50 km/h
[kPa]	[PSI]				[2.5 mph]	[5 mph]	[10 mph]	[12.5 mph]	[16 mph]	[20 mph]	[22 mph]	[25 mph]	[28 mph]	[30 mph]
120	17		2635		1910*	1720**	1535	1410	1270	1225	1180	1145	1100	1040
160	23		3195		2320*	2085**	1865	1710	1545	1485	1430	1390	1335	1265
200	29		3510		2545*	2290**	2045	1875	1695	1630	1570	1525	1465	1390
240	35		4070		2955*	2655**	2370	2175	1965	1895	1825	1770	1700	1610
280	41		4635		3365*	3025**	2700	2480	2235	2155	2075	2015	1935	1835
320	46		5200		3775*	3390**	3030	2780	2510	2420	2330	2260	2170	2055
360	52		5705		4140*	3720**	3325	3050	2755	2655	2555	2480	2380	2255
400	58	143	6270		4550*	4090**	3650	3350	3025	2915	2805	2725	2615	2480

### 340/80-18 IND : Constant load service (Transport)

Inflation Pressure		Load Index (A8)	Static	Creep [1]	5 km/h	10 km/h	15 km/h	20 km/h	25 km/h	30 km/h	35 km/h	40 km/h	45 km/h	50 km/h
[kPa]	[PSI]				[2.5 mph]	[5 mph]	[10 mph]	[12.5 mph]	[16 mph]	[20 mph]	[22 mph]	[25 mph]	[28 mph]	[30 mph]
120	17		2635		1660	1430	1295	1250	1215	1190	1170	1145	1100	1040
160	23		3195		2015	1740	1570	1515	1475	1445	1420	1390	1335	1265
200	29		3510		2210	1905	1725	1660	1615	1585	1555	1525	1465	1390
240	35		4070		2565	2215	2000	1930	1875	1840	1805	1770	1700	1610
280	41		4635		2920	2520	2275	2195	2135	2095	2055	2015	1935	1835
320	46		5200		3275	2825	2555	2465	2395	2350	2305	2260	2170	2055
360	52		5705		3595	3100	2800	2705	2630	2580	2530	2480	2380	2255
400	58	143	6270		3950	3405	3080	2970	2890	2835	2780	2725	2615	2480

[1] Creep means a movement of equipment at a very low speed (commonly not over 120 m in 60 minutes)

\* Cyclic: One way distance up to 150 m (500 feet); \*\* Cyclic: One way distance up to 600 m (2000 feet)

IMPORTANT: Recommendations and technical data are subject to change without prior notice.

# Camso MPT 732



## Load capacity per tire in kilogram (kg)

### 400/70-20 IND : Cyclic load service (Pick & Carry)

Inflation Pressure		Load Index (A8)	Static	Creep [1]	5 km/h	10 km/h	15 km/h	20 km/h	25 km/h	30 km/h	35 km/h	40 km/h	45 km/h	50 km/h
[kPa]	[PSI]				[2.5 mph]	[5 mph]	[10 mph]	[12.5 mph]	[16 mph]	[20 mph]	[22 mph]	[25 mph]	[28 mph]	[30 mph]
200	29		4185		3040*	2730**	2440	2240	2020	1945	1875	1820	1745	1655
240	35		4865		3530*	3175**	2835	2600	2350	2265	2180	2115	2030	1925
280	41		5530		4015*	3610**	3225	2960	2670	2575	2475	2405	2310	2190
320	46		6210		4510*	4050**	3620	3320	2995	2890	2780	2700	2590	2455
360	52		6810		4945*	4440**	3965	3640	3285	3165	3050	2960	2840	2695
400	58		7475		5430*	4875**	4355	4000	3610	3480	3350	3250	3120	2960
450	65		8110		5110*	4405**	3985	3840	3735	3665	3595	3525	3385	3210
500	73	155	8915		6470*	5815**	5195	4765	4300	4145	3990	3875	3720	3525

### 400/70-20 IND : Constant load service (Transport)

Inflation Pressure		Load Index (A8)	Static	Creep [1]	5 km/h	10 km/h	15 km/h	20 km/h	25 km/h	30 km/h	35 km/h	40 km/h	45 km/h	50 km/h
[kPa]	[PSI]				[2.5 mph]	[5 mph]	[10 mph]	[12.5 mph]	[16 mph]	[20 mph]	[22 mph]	[25 mph]	[28 mph]	[30 mph]
200	29		4185		2640	2275	2055	1985	1930	1895	1855	1820	1745	1655
240	35		4865		3065	2645	2390	2305	2240	2200	2155	2115	2030	1925
280	41		5530		3485	3005	2720	2620	2550	2500	2455	2405	2310	2190
320	46		6210		3915	3375	3050	2945	2860	2810	2755	2700	2590	2455
360	52		6810		4290	3700	3345	3225	3140	3080	3020	2960	2840	2695
400	58		7475		4715	4065	3675	3545	3445	3380	3315	3250	3120	2960
450	65		8110		5110	4405	3985	3840	3735	3665	3595	3525	3385	3210
500	73	155	8915		5620	4845	4380	4225	4110	4030	3955	3875	3720	3525

[1] Creep means a movement of equipment at a very low speed (commonly not over 120 m in 60 minutes)

\* Cyclic: One way distance up to 150 m (500 feet); \*\* Cyclic: One way distance up to 600 m (2000 feet)

IMPORTANT: Recommendations and technical data are subject to change without prior notice.

# Camso MPT 732



## Load capacity per tire in kilogram (kg)

### 440/80-24 IND : Cyclic load service (Pick & Carry)

Inflation Pressure		Load Index (A8)	Static	Creep [1]	5 km/h	10 km/h	15 km/h	20 km/h	25 km/h	30 km/h	35 km/h	40 km/h	45 km/h	50 km/h
[kPa]	[PSI]				[2.5 mph]	[5 mph]	[10 mph]	[12.5 mph]	[16 mph]	[20 mph]	[22 mph]	[25 mph]	[28 mph]	[30 mph]
120	17		4315		3130*	2815**	2515	2305	2080	2005	1930	1875	1800	1705
160	23		5265		3825*	3435**	3070	2815	2540	2450	2360	2290	2200	2085
200	29		5785		4200*	3775**	3370	3095	2790	2690	2590	2515	2415	2290
240	35		6820		4950*	4450**	3975	3645	3290	3175	3055	2965	2845	2700
280	41		7680		5580*	5010**	4475	4110	3705	3575	3440	3340	3205	3040
320	46	154	8625		6265*	5625**	5025	4615	4165	4015	3865	3750	3600	3415

### 440/80-24 IND : Constant load service (Transport)

Inflation Pressure		Load Index (A8)	Static	Creep [1]	5 km/h	10 km/h	15 km/h	20 km/h	25 km/h	30 km/h	35 km/h	40 km/h	45 km/h	50 km/h
[kPa]	[PSI]				[2.5 mph]	[5 mph]	[10 mph]	[12.5 mph]	[16 mph]	[20 mph]	[22 mph]	[25 mph]	[28 mph]	[30 mph]
120	17		4315		2720	2345	2120	2045	1990	1950	1915	1875	1800	1705
160	23		5265		3320	2865	2590	2495	2425	2380	2335	2290	2200	2085
200	29		5785		3645	3145	2840	2740	2665	2615	2565	2515	2415	2290
240	35		6820		4300	3705	3350	3230	3145	3085	3025	2965	2845	2700
280	41		7680		4845	4175	3775	3640	3540	3475	3405	3340	3205	3040
320	46	154	8625		5440	4690	4240	4090	3975	3900	3825	3750	3600	3415

[1] Creep means a movement of equipment at a very low speed (commonly not over 120 m in 60 minutes)

\* Cyclic: One way distance up to 150 m (500 feet); \*\* Cyclic: One way distance up to 600 m (2000 feet)

IMPORTANT: Recommendations and technical data are subject to change without prior notice.

# Camso MPT 732



## Load capacity per tire in kilogram (kg)

### 500/70-24 IND : Cyclic load service (Pick & Carry)

Inflation Pressure		Load Index (A8)	Static	Creep [1]	5 km/h	10 km/h	15 km/h	20 km/h	25 km/h	30 km/h	35 km/h	40 km/h	45 km/h	50 km/h
[kPa]	[PSI]				[2.5 mph]	[5 mph]	[10 mph]	[12.5 mph]	[16 mph]	[20 mph]	[22 mph]	[25 mph]	[28 mph]	[30 mph]
120	17		4750		3450*	3100**	2765	2540	2290	2210	2125	2065	1980	1880
160	23		5785		4200*	3775**	3370	3095	2790	2690	2590	2515	2415	2290
200	29		6360		4620*	4150**	3705	3400	3070	2960	2850	2765	2655	2515
240	35		7500		5445*	4890**	4370	4010	3620	3490	3360	3260	3130	2965
280	41		8440		6130*	5505**	4920	4515	4075	3925	3780	3670	3525	3340
320	46	157	9490		6890*	6190**	5530	5075	4580	4415	4250	4125	3960	3755

### 500/70-24 IND : Constant load service (Transport)

Inflation Pressure		Load Index (A8)	Static	Creep [1]	5 km/h	10 km/h	15 km/h	20 km/h	25 km/h	30 km/h	35 km/h	40 km/h	45 km/h	50 km/h
[kPa]	[PSI]				[2.5 mph]	[5 mph]	[10 mph]	[12.5 mph]	[16 mph]	[20 mph]	[22 mph]	[25 mph]	[28 mph]	[30 mph]
120	17		4750		2995	2580	2335	2250	2190	2150	2105	2065	1980	1880
160	23		5785		3645	3145	2840	2740	2665	2615	2565	2515	2415	2290
200	29		6360		4010	3455	3125	3015	2930	2875	2820	2765	2655	2515
240	35		7500		4725	4075	3685	3555	3455	3390	3325	3260	3130	2965
280	41		8440		5320	4590	4145	4000	3890	3815	3745	3670	3525	3340
320	46	157	9490		5980	5155	4660	4495	4375	4290	4210	4125	3960	3755

[1] Creep means a movement of equipment at a very low speed (commonly not over 120 m in 60 minutes)

\* Cyclic: One way distance up to 150 m (500 feet); \*\* Cyclic: One way distance up to 600 m (2000 feet)

IMPORTANT: Recommendations and technical data are subject to change without prior notice.

# Camso MPT 732



## Load capacity per tire in kilogram (kg)

### 480/80-26 IND : Cyclic load service (Pick & Carry)

Inflation Pressure		Load Index (A8)	Static	Creep [1]	5 km/h	10 km/h	15 km/h	20 km/h	25 km/h	30 km/h	35 km/h	40 km/h	45 km/h	50 km/h
[kPa]	[PSI]				[2.5 mph]	[5 mph]	[10 mph]	[12.5 mph]	[16 mph]	[20 mph]	[22 mph]	[25 mph]	[28 mph]	[30 mph]
120	17		5175		3760*	3375**	3015	2770	2500	2410	2320	2250	2160	2050
160	23		6315		4585*	4120**	3680	3375	3045	2935	2825	2745	2635	2500
200	29		6935		5035*	4525**	4040	3710	3345	3225	3105	3015	2895	2745
240	35		8175		5935*	5335**	4765	4375	3945	3805	3660	3555	3415	3235
280	41		9210		6690*	6010**	5365	4925	4445	4285	4125	4005	3845	3645
320	46	160	10350		7515*	6750**	6030	5535	4995	4815	4635	4500	4320	4095

### 480/80-26 IND : Constant load service (Transport)

Inflation Pressure		Load Index (A8)	Static	Creep [1]	5 km/h	10 km/h	15 km/h	20 km/h	25 km/h	30 km/h	35 km/h	40 km/h	45 km/h	50 km/h
[kPa]	[PSI]				[2.5 mph]	[5 mph]	[10 mph]	[12.5 mph]	[16 mph]	[20 mph]	[22 mph]	[25 mph]	[28 mph]	[30 mph]
120	17		5175		3265	2815	2545	2455	2385	2340	2295	2250	2160	2050
160	23		6315		3980	3430	3100	2990	2910	2855	2800	2745	2635	2500
200	29		6935		4370	3770	3405	3285	3195	3135	3075	3015	2895	2745
240	35		8175		5155	4445	4015	3875	3770	3695	3625	3555	3415	3235
280	41		9210		5805	5005	4525	4365	4245	4165	4085	4005	3845	3645
320	46	160	10350		6525	5625	5085	4905	4770	4680	4590	4500	4320	4095

[1] Creep means a movement of equipment at a very low speed (commonly not over 120 m in 60 minutes)

\* Cyclic: One way distance up to 150 m (500 feet); \*\* Cyclic: One way distance up to 600 m (2000 feet)

IMPORTANT: Recommendations and technical data are subject to change without prior notice.

# Camso MPT 732



## Load capacity per tire in kilogram (kg)

### 440/80-28 IND : Cyclic load service (Pick & Carry)

Inflation Pressure		Load Index (A8)	Static	Creep [1]	5 km/h	10 km/h	15 km/h	20 km/h	25 km/h	30 km/h	35 km/h	40 km/h	45 km/h	50 km/h
[kPa]	[PSI]				[2.5 mph]	[5 mph]	[10 mph]	[12.5 mph]	[16 mph]	[20 mph]	[22 mph]	[25 mph]	[28 mph]	[30 mph]
120	17		4600		3340*	3000**	2680	2460	2220	2140	2060	2000	1920	1820
160	23		5610		4075*	3660**	3270	3000	2710	2610	2515	2440	2340	2220
200	29		6165		4475*	4020**	3590	3295	2975	2870	2760	2680	2575	2440
240	35		7270		5275*	4740**	4235	3885	3510	3380	3255	3160	3035	2875
280	41		8190		5945*	5340**	4770	4380	3950	3810	3665	3560	3420	3240
320	46	156	9200		6680*	6000**	5360	4920	4440	4280	4120	4000	3840	3640

### 440/80-28 IND : Constant load service (Transport)

Inflation Pressure		Load Index (A8)	Static	Creep [1]	5 km/h	10 km/h	15 km/h	20 km/h	25 km/h	30 km/h	35 km/h	40 km/h	45 km/h	50 km/h
[kPa]	[PSI]				[2.5 mph]	[5 mph]	[10 mph]	[12.5 mph]	[16 mph]	[20 mph]	[22 mph]	[25 mph]	[28 mph]	[30 mph]
120	17		4600		2900	2500	2260	2180	2120	2080	2040	2000	1920	1820
160	23		5610		3540	3050	2755	2660	2585	2540	2490	2440	2340	2220
200	29		6165		3885	3350	3030	2920	2840	2785	2735	2680	2575	2440
240	35		7270		4580	3950	3570	3445	3350	3285	3225	3160	3035	2875
280	41		8190		5160	4450	4025	3880	3775	3700	3630	3560	3420	3240
320	46	156	9200		5800	5000	4520	4360	4240	4160	4080	4000	3840	3640

[1] Creep means a movement of equipment at a very low speed (commonly not over 120 m in 60 minutes)

\* Cyclic: One way distance up to 150 m (500 feet); \*\* Cyclic: One way distance up to 600 m (2000 feet)

IMPORTANT: Recommendations and technical data are subject to change without prior notice.