

FL 252 - Технические спецификации



Description

Шины FL 252 подходят для роторных сенных граблей/ сеноворошилок, используемых для сеноуборочных работ, а также для вилочных погрузчиков, задействованных в логистических операциях. Эти шины обладают исключительной долговечностью, тогда как особый рисунок протектора обеспечивает максимальную устойчивость во время подъемных работ.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Роторные грабли / Сеноворошилка
Производство: Вилочный погрузчик

Version	STANDARD
Type	TT
Tyre Size	8.25 - 15

Dimensions International Standard

Ply Rating	14
Section Width (mm)	240
Overall Diameter (mm)	855
Rim Rec	6.50
Rim Alt	7.0

Load capacity (Kg)

	km/h / bar	8.00
25 LOAD WHEEL		4225
25 STEER WHEEL		3250
10 OTHER VEHICLES		4225
25 OTHER VEHICLES		3250
STATIC SIDE LOADER		4910

Printed on 07.06.2023 21:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..